









STEADICAM® SYSTEMS CONFIGURATIONS

Camera Stabilizing Systems

DESCRIPTION	Flyer Red	Flyer LE SE	Flyer 24 LEHD	Flyer LE	Pilot Sled (sled only)	Pilot	Merlin Arm & Vest	Merlin
Maximum Camera / Load Weight (Note: weights are approximate & conversions are rounded)	 19lbs / 8.6kg	 19lbs / 8.6kg	 19lbs / 8.6kg	 19lbs / 8.6kg	 10lbs / 4.5kg	 10lbs / 4.5kg	 7.5lbs / 3.4kg	 5lbs / 2.3kg
Dynamically Balanced Sled	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Telescopic Post	2-Section	2-Section	2-Section	2-Section	2-Section	2-Section	N/A	N/A
Post Length	18.5-32in / 47-81cm	18.5-32in / 47-81cm	18.5-32in / 47-81cm	18.5-32in / 47-81cm	20.5-33.5in / 52-85cm	20.5-33.5in / 52-85cm	N/A	N/A
Low Friction Gimbal	Standard	Standard	Standard	Standard	Standard	Standard	N/A	N/A
Merlin Metal Gimbal	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Standard
HD 7" Color TFT Monitor	Standard	N/A	Standard	N/A	N/A	N/A	N/A	N/A
TFT 7" Color Monitor 700nits AR coating	N/A	Standard	N/A	Option	N/A	N/A	N/A	N/A
TFT 7" Color Monitor 500nits AR coating	N/A	N/A	N/A	Standard	N/A	N/A	N/A	N/A
TFT 5.8" Color Monitor	N/A	N/A	N/A	N/A	Standard	Standard	N/A	N/A
Electronic Frameline Generator in Monitor	Standard Fixed	Standard Adjustable	Standard Fixed	N/A	N/A	N/A	N/A	N/A
Adjustable Monitor Bracket	Standard	Standard	Standard	Standard	Standard	Standard	N/A	N/A
Iso-Elastic Arm Type	Flyer Arm	Flyer Arm	Flyer Arm	Flyer Arm	N/A	Pilot Arm	Merlin Arm	N/A
Boom Range	30in / 76.2cm	30in / 76.2cm	30in / 76.2cm	30in / 76.2cm	N/A	24in / 61cm	24in / 61cm	
Flyer Vest	Standard	N/A	Standard	Standard	N/A	N/A	N/A	N/A
Leather Flyer Vest	N/A	Standard	N/A	N/A	N/A	N/A	N/A	N/A
Pilot, Merlin Ultra Low Profile Vest	N/A	N/A	N/A	N/A	N/A	Standard	Standard	N/A
Power Cube Battery Kit	Standard	Standard	Option	Option	N/A	N/A	N/A	N/A
V-lock Battery Adapter	Standard	Standard	Option	Standard	Option	Option	N/A	N/A
AB Battery Adapter	N/A	N/A	Option	Option	Option	Option	N/A	N/A
Pen cell / AA Battery Power	N/A	N/A	N/A	N/A	Option	Option	N/A	N/A
24V Power System	Standard	Standard	Standard	Standard	N/A	N/A	N/A	N/A
Low Mode Kit	Standard	Standard	Available	Available	Available	Available	N/A	N/A
Balance / Operation Stand	Standard	Standard	Standard	Standard	Available	Available	Available	Available
Hard Carrying Case	Standard	Standard	Option	Option	N/A	N/A	N/A	N/A
Soft Carrying Case	N/A	N/A	Standard	Standard	Backpack	Backpack	N/A	Standard

STANDARD = Item or feature is supplied with product as a default. OPTION = Item or feature can be incorporated into product order code. N/A = Item or feature is not available or not applicable to product. AVAILABLE = Item or feature can be ordered as separate line item.

The Tiffen Company • 90 Oser Avenue, Hauppauge, NY 11788 • Tel: 1-631-273-2500 • Fax: 1-631-273-2557 • e-mail: steadicam@tiffen.com • www.tiffen.com

Steadicam Manufacturing: 6933 San Fernando Road, Glendale, CA 91201 • Telephone 818-843-4600 x7913 • Fax: 818-843-8321 • Prices net FOB Los Angeles.








Robin Thwaites - International Director of Sales: Tiffen International Ltd., Unit 5, Avonbury Business Park, Howes Lane, Bicester, Oxfordshire, OX26 2UA, United Kingdom

Tel: +44 (0) 870 100 1220 • Fax: +44 (0) 1869 321 766 • e-mail: info@flysteadicam.com

All prices and specifications subject to change without notice. STEADICAM® is a registered trademark of The Tiffen Company. All other trademarks are the property of their respective owners. VISIT US AT WWW.STEADICAM.COM

STEADICAM® SYSTEMS CONFIGURATIONS

Camera Stabilizing Systems

DESCRIPTION	Ultra ² Cine	Ultra ² C	Clipper 324	Clipper 312	Archer ² SE	Archer ² S	Archer ²
Maximum Camera / Load Weight (Note: weights are approximate & conversions are rounded)	 48lbs/22kg	 48lbs/22kg	 35lbs/16kg	 35lbs/16kg	 30lbs/13.6kg	 30lbs/13.6kg	 26lbs/11.8kg
Dynamically Balanced Sled	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Telescopic Post	4-Section	4-Section	3-Section	3-Section	2-Section	2-Section	2-Section
Post Length	28-72in / 71-183cm	28-72in / 71-183cm	26-49in / 66-124.5cm	26-49in / 66-124.5cm	23-35.5in / 58-90cm	23-35.5in / 58-90cm	23-35.5in / 58-90cm
Ultra Low Friction Gimbal	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Tilt Head	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Motorized Stage	Dual Axis Standard	Option	Option	Option	Dual Axis Standard	Single Axis Standard	Option
HD UltraBrite2, 8.4" Color TFT Monitor	Standard	Option	Option	Option	Option	Option	Option
HD 7" Color TFT Monitor	Option	Option	Option	Option	Option	Option	Option
TFT 7" Color Monitor 700nits AR coating	Option	Standard	Standard	Standard	Standard	Standard	Standard
Electronic Frameline Generator in Monitor	Standard Adjustable	Standard Adjustable	Option	Option	Standard Adjustable	Standard Adjustable	Standard Adjustable
Adjustable Monitor Bracket	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Adjustable Electronic Frameline Generator in Sled	Standard	Standard	Standard	Standard	N/A	N/A	N/A
Artificial Horizon	Standard	Option	Standard	Option	N/A	N/A	N/A
On-board Battery Status Display	Standard	Standard	N/A	N/A	N/A	N/A	N/A
Arm Type	G-70	G-70	G-50	G-50	G-50	G-50	G40
Boom Range	29in / 74cm	29in / 74cm	29in / 74cm	29in / 74cm	29in / 74cm	29in / 74cm	29in / 74cm
Lightweight Ultra Vest	Standard	Standard	Option	Option	Option	Option	Option
Leather LX Vest	N/A	N/A	N/A	N/A	Standard	N/A	N/A
Lightweight LX Vest	N/A	N/A	Standard	Standard	N/A	Standard	Standard
Power Cube Battery Kit	Standard	Available	Standard	Available	Standard	Available	Available
Anton Bauer Battery Kit	N/A	Available	N/A	Available	Available	Available	Available
V-lock Battery Adapter	Standard	Option	Standard	Option	Option	Option	Option
AB Battery Adapter	Option	Option	Option	Option	Option	Option	Option
24V Power System	Standard	Standard	Standard	N/A	Standard	Standard	Standard
Low Mode Kit	Option	Option	Option	Option	Standard	Standard	Option
Balance / Operation Stand	Option	Option	Option	Option	Standard	Standard	Option
Hard Carrying Case	Standard	Standard	Standard	Standard	Standard	Standard	Standard

STANDARD = Item or feature is supplied with product as a default. OPTION = Item or feature can be incorporated into product order code. N/A = Item or feature is not available or not applicable to product. AVAILABLE = Item or feature can be ordered as separate line item.

The Tiffen Company • 90 Oser Avenue, Hauppauge, NY 11788 • Tel: 1-631-273-2500 • Fax: 1-631-273-2557 • e-mail: steadicam@tiffen.com • www.tiffen.com

Steadicam Manufacturing: 6933 San Fernando Road, Glendale, CA 91201 • Telephone 818-843-4600 x7913 • Fax: 818-843-8321 • Prices net FOB Los Angeles.

Robin Thwaites - International Director of Sales: Tiffen International Ltd., Unit 5, Avonbury Business Park, Howes Lane, Bicester, Oxfordshire, OX26 2UA, United Kingdom

Tel: +44 (0) 870 100 1220 • Fax: +44 (0) 1869 321 766 • e-mail: info@flysteadicam.com

All prices and specifications subject to change without notice. STEADICAM® is a registered trademark of The Tiffen Company. All other trademarks are the property of their respective owners. VISIT US AT WWW.STEADICAM.COM